



SPECIFICATIONS

SPECIFICATIONS	
DIMENSIONS(L/W/H)	2000MM*730MM*1050MM
WHEELBASE	1380MM
MIN. GROUND CLEARANCE	160MM
SEAT HEIGHT	785MM
MAX. LOAD	166KG
FUEL TANK	17L
ENGINE TYPE	SINGLE CYLINDER 4 STROKE, WATER COOLED, 292.4CC
MAX. NET POWER/CORRESPONDING SPEED	21.4KW/29.1PS/8750RPM
MAX. TORQUE/CORRESPONDING SPEED	25.3N.M/7250RPM
BORE*STROKE	78MM*61.2MM
COMRESSION RATIO	11:0:1
FUEL SUPPLY METHOD	EFI
SWING ARM	SINGLE SIDED ALUMINUM SWING ARM
ABS	DUAL-CHANNEL ABS
LIGHT	LED
DASHBOARD	5 INCH FULLY LAMINATED TFT, IPS FULL-VIEW INSTRUMENT DISPLAY
FRONT/BACK TIRE	110/70R17 - 150/60R17
FRONT BRAKING SYSTEM	300MM SINGLE DISK FLOATING DISK, FOUR-PISTON RADIAL CALIPER
REAR BARKING SYSTEM	260MM SINGLE DISK, DOUBLE PISTON FLOATING CALIPER
FRONT SUSPENSION SYSTEM	INVERTED HYDRAULIC DAMPING TYPE SHOCK ABSORPTION
REAR SUSPENSION SYSTEM	ZERO LINK SUSPENSION
FRONT/BACK CONTROLS	CNC TWO-STAGE ADJUSTABLE FRONT CONTROL, FORGED REAR CONTROL
FUEL TANK	LARGE CAPACITY POLYMER COMPOSITE FUEL TANK



removal of wheels empowering competition convenience on the racetrack.







DIMENSIONS







UNIQUELY DIFFERENT

www.fkmotors.com